

MOTOR GREDER

CLG 422



DIMENZIJE

MODEL		CLG 416	CLG 418	CLG 422
Težina	kg	14.100	15.500	18.500
Motor		Cummins	Cummins	Cummins
Model motora		Q585.9-C173	6CAT8.3-C215	6CAT8.3-C215
Snaga motora	kw/ks	129 / 175	160 / 217	172 / 235
Zapremina motora	L	5,9	8,3	8,3
Cilindri		6	6	6
Otvor x Hod	mm	102 X 120	114 X 135	114 X 135
Transmisija		Z / F	Z / F	Z / F
Brzine		6 Napred / 3 Nazad	6 Napred / 3 Nazad	6 Napred / 3 Nazad
Gume		17,5-25	17,5-25	17,5-25
Grederski nož	mm	650 x 3960	650 x 3960	610 x 4270
Klizanje noža desno/levo	mm	725 / 675	725 / 675	725 / 675
Zazor noža od zemlje	mm	450	450	450
Dubina sečenja noža	mm	555	555	555
Ugao upravljanja		+/-45	+/-45	+/-45
Ugao savijanja zgloba lasice		+/-20	+/-20	+/-20
Oscilacije		+/-15	+/-15	+/-15

VALJCI

CLG 604T



CLG 613T



CLG 614H



DIMENZIJE

MODEL		612 H	614 H	604 T	613 T
Težina	kg	12.300	14.000	4.400	13.500
Motor		Cummins	Cummins	Deutz	Cummins
Model motora		B75.9-C	B5.9-C	F3L2011	4BT3.9
Zapremina motora	L	5,9	5,9	2,3	3,9
Snaga motora	kw/ks	108 / 145	108 / 145	33,9 / 46	93 / 126
Cilindri		6	6	3	4
Savlađavanje uspona	%	50	50	41	30-35
Prečnik pegle	mm	1500	1470	800	1214
Širina pegle	mm	2130	2130	1300	2130
Hid. rezervoar	L	120	120	54	110
Rezervoar za gorivo	L	300	300	65	200
Rezervoar za vodu	L			200	920
Brzina	km/sat	0-12	0-12	0-10,5	0-13

BULDOZER

B 320 Y



DIMENZIJE

MODEL		TY 160	TY 180CA	TY 220 C	B 320Y
Težina	kg	17.860+16.000	18.512+2100	25.500+2800	34.000+5350
Dimenzije noža	S x V	3416X1150	3416X1150	3725X1315	4130X1590
Motor		Cummins	Cummins	Cummins	Cummins
Snaga motora	kw/ks	122/165	132,4/180	162/220	239/325
Cilindri		6	6	6	6
Otvor x Hod	mm	139,7X152,4	139,7X152,4	139,7X152,4	139,7X152,4
Širina papuče	mm	560	510	560	560
Zapremina noža	m ²	3,85	3,88	5,6	7
1 stepen prenosa napred	km / sat	3,8	3,9	3,6	3,6
2 stepen prenosa napred	km / sat	6,6	6,8	6,5	6,6
3 stepen prenosa napred	km / sat	10,6	10,9	11,2	11,5
1 stepen prenosa unazad	km / sat	4,9	5,0	4,3	4,4
2 stepen prenosa unazad	km / sat	8,5	8,6	7,7	7,8
3 stepen prenosa unazad	km / sat	13,6	13,7	13,2	13,5

KOMBINIRKA



Operativna težina	: 8000 +/- 300 kg
Motor	: Deutz
Model motora	: TD2268-4
Nom. snaga	: 70kw/95hp
Zapremina motora	: 4,16 lt
Otvor x Hod	: 95x115 mm
Cilindri	: 4 cilindara
Bagerska kasika	: 0,21 m ³
Visina istresanja	: 2670 +/- 20 mm
Utovarivačka kasika	: 1,0 m ³
Maks. dubina kopanja	: 4380 mm
4 brzine napred	: 36 km/sat
4 brzine nazad	: 38 km/sat
Gume prednje	: 10,5x18
Gume zadnje	: 16,9x28

MINI UTOVARIVAČ

CLG 375



Operativna težina	: 3.460 kg
Motor	: Cummins
Model motora	: 4BT3.3
Nom. snaga	: 56kw/75hp
Zapremina motora	: 3,3 lt
Otvor x Hod	: 95x115 mm
Cilindri	: 4 cilindara
Nom. opterećenje	: 907 kg
Grafično opterećenje	: 1814 kg
Kapacitet kasike	: 0,5 m ³
Gume	: 12 x 16,5
Brzina	: 11 km/sat