



ZF osovine



SPECIFIKACIJA		835	842	856	862	877 III	888	
Model		Cummins	Cummins	Cummins	Cummins	Cummins	Cummins	
Motor		6BT5.9	B5.9-C	6CTA8.3-C215	6CTA8.3-C240	QSM11-C290	M11-C310	
Snaga motora	kw(kilopow)/a/min	92(123)@2200	123(165)@2200	160(215)@2200	179(240)@2200	216(290)@2100	231(310)@2100	
Transmisija		ZF 4WG180	ZF 4WG180	ZF 4WG180	ZF 4WG200	ZF 4WG200	ZF 4WG308	
Maksimalna brzina	km/h	36	37	37	37	37	35	
Diferencijal		ograničeno proklizavanje	ograničeno proklizavanje	ograničeno proklizavanje ZF AP400	ograničeno proklizavanje	ograničeno proklizavanje	ograničeno proklizavanje ZF AP420/5%	
Hidraulika	Proizvođač	Kawasaki	Kawasaki	Kawasaki	Kawasaki	Kawasaki	Kawasaki	
	Vreme ciklusa	5	9	10,5	11,5	11,6	11,6	
Kapacitet	kašike	m ³	1,7	2,3	3,0	3,5	4	
	Nominalno opterećenje	kg	3000	4000	5000	6000	7000	8000
Dimenzije	Visina istresanja	mm	2911	2900	3100	3150	3200±50	3300±50
	Doljevat istovara @ 45°	mm	1080	1034	1035	1200	1300±50	1513±50
	Ukupna dužina	mm	6260	7257	8060	8480	9075±50	9350±50
	Ukupna širina	mm	2456	2766	2976	3010	3150±30	3445±30
Visina krova kabine	mm	3238	3347	3467	3467	3580±40	3852±40	
Težina	kg	10900	13700	16800	19200±500	23500±500	28500	
Gume		17,5-25	20,5-25	23,5-25	23,5-25	26,5-25	29,5-25	

Standardna oprema: klima, Fops/Rops kabina, kasetofon. Sve navedene mašine dostupne su sa Euro 2 i Euro 3 motorom.
Najvažnije komponente: Cummins motor, ZF osovine i transmisija, Kawasaki hidraulika, Siemens elektronika.

