



8m³ Truck Mixer



Drum Geometrical Volume	13.4 m ³
Drum Agitating Capacity	8 m ³
Concrete Feeding Speed	≥3 m ³ /min
Concrete Discharging Speed	≥2.7 m ³ /min
Drum Remnant Ratio	<0.5%
Drum Inclined Angle	13°
Water Reservoir Capacity	450 L
Water Supply Type	Pneumatic Pressure

8m³ Concrete Truck Mixer



SPECIFICATIONS

Drum geometrical capacity	m ³	13.4
Drum agitating capacity	m ³	8
Concrete feeding speed	m ³ /min	≥3
Concrete discharging speed	m ³ /min	≥2.7
Drum remnant ratio	%	0.5
Drum revolution	r/min	0-14
Drum inclined angle	°	13
Water reservoir capacity	L	450
Hydraulic reservoir capacity	L	18
Hydraulic system pressure	MPa	35
Upper structure weight	kg	3700

CHASSIS OPTIONS

Sinotruk	HOWO ZZ1257N3847C		
Engine model	WD615.95E		
Emission	Euro III		
Rated power	kW	247	
Displacement	ml	9726	
Shacman	DELONG SX5255GJBJR364		
Engine model	WP10.336N		
Emission	Euro III		
Rated power	kW	247	
Displacement	ml	9726	

HYDRAULICS

	Standard		Optional	
Hydraulic pump	SAUER	KPV23-674R	ARK REXROTH	PV089 A4VTG90
Hydraulic motor	SAUER	KMF23-516-50	ARK REXROTH	MF089 AA2FM80
Speed reducer	SAUER	TMG61.2	TOP ZF	P68 P5300

Model	L1 (mm)	W1 (mm)	H1 (mm)	Weight (kg)
8m ³ SINOTRUK	8580	2496	3780	25000
8m ³ SHACMAN	8850	2496	3780	25000



Guangxi Liugong Machinery Co., Ltd.

No. 1 Liutai Road, Liuzhou, Guangxi 545007, PR China

T: +86 772 388 6124 E: overseas@liugong.com

www.liugong.com

11/2012 Designed by LiuGong

Specifications and designs are subject to change without notice. Machines shown may include optional equipment.